



MRA50019

Key Features:

- 19 dBi Directional Gain
- Integrated enclosure
- LED window display at the bottom
- Special Outdoor Weatherproof Enclosure Dedicated for Mikrotik RouterBOARDS
- High Quality Construction
- Horizontal or Vertical Polarization
- Wall Mounting Optional
- Tilt Adjustment Optional
- 5 Years Warranty
- Designed for All Weather Operation



Applications:

- 5 GHz Band Wireless LAN
- IEEE 802.11a WLAN Systems
- RLAN
- FWA
- WiMAX

Description:

Antenna with integrated enclosure working in 5 GHz band with 19 dBi gain that can be mounted for horizontal or vertical polarization. The range includes weatherproof outdoor enclosure with panel antenna and enough compartment for RouterBoard or any other electronic equipment. Enclosure is furnished with special cable gland connector with an easy connection to Internet Network. Ethernet cable can be plugged in without removing the RJ45. Perfectly designed for operation under severe weather conditions. Proper materials allow operation in the salty water environment without corrosion. High quality construction of pole mounting elements guarantee easy elevation and easy tilt down as well as rock-stable operation. It can be used as customer premise equipment and also as small base stations. Inside the enclosure are suitable posts for Mikrotik RouterBOARDS 411 and 711 series.

Electrical Properties	
Frequency	5.1 - 5.9 GHz
Gain	19dBi
Polarization	horizontal or vertical
Beamwidth deg horizontal	20°
Beamwidth deg vertical	20°
VSWR	<1.7
Impedance	50 ohm
Front to back ratio	> 33 dB
Lightning protection:	DC ground
Enclosure Properties	
Technology:	Microstrip
Material:	UV protected
Colour:	Grey
Ingress Protection (EN 60529):	IP 66
Min temperature:	-40°C / -40°F
Max temperature:	80°C / 176°F
Mechanical Properties	
Compatible with:	RB411 and RB711 series
Input Connector	UFL pigtail (or MMCX optional)
Enclosure Connector	Cable Gland
Outsite Dimensions	180x180x45mm / 7,2x7,2x1,8"
Weight	0,6kg / 1,3lbs

Specification subject to change without notice.